

CLAIMS

1. A chip resistor comprising:

an insulating chip substrate including an upper surface
5 and a pair of opposite side surfaces;

a resistor film formed on the upper surface of the insulating
substrate;

a pair of upper electrodes formed from silver-based
conductive paste on the upper surface of the insulating substrate
10 to be connected to the resistor film;

a cover coat covering the resistor film;

an auxiliary electrode formed on each of the upper
electrodes to partially overlap the cover coat;

a side electrode formed on each of the side surfaces of
15 the insulating substrate and electrically connected to one of
the upper electrodes and one of the auxiliary upper electrodes;

a nickel-plated layer covering the auxiliary electrode
and the side electrode; and

a soldering layer covering the nickel-plated layer and
20 formed of tin or solder;

wherein the side electrode is made of nonmagnetic
conductive resin paste, the auxiliary upper electrode being
made of carbon-based conductive resin paste.

25 2. The chip resistor according to claim 1, wherein the side
electrode is made of carbon-based conductive resin paste.

3. The chip resistor according to claim 1, further comprising a pair of lower electrodes formed on a lower surface of the insulating substrate and connected to the side electrodes; wherein the lower electrodes are formed from a carbon-based
5 conductive resin paste and covered with a nickel-plated underlying layer and a soldering layer.

4. The chip resistor according to claim 1, further comprising an overcoat covering the cover coat and partially overlapping
10 the auxiliary upper electrodes.

5. The chip resistor according to claim 1, wherein the auxiliary upper electrode is formed with a cutout in which the side electrode is connected to the upper electrode.